


SBC



PSB-873LF

PICMG 1.3 Full Size CPU Card supports 3rd/2nd Gen. Intel® Core™ i7/ i5/ i3 Pentium® CPU with VGA/ Audio/ LAN/ 2COM

Features :

- Supports 3rd/2nd generation Intel® Core™ i7/ i5/ i3 Processor
- Equipped with Intel® H61 chipset
- Memory supports DDR3 1333/1600 DIMM up to 16GB
- Supports Single Gigabit Ethernet
- Supports USB 2.0
- Supports Trusted Platform Module



Protech Systems Co., Ltd.

No. 24, Lane 365, Yang Goang Street, Nei Hu District Taipei 114, Taiwan
TEL: +886-2-8751-1111 FAX: +886-2-8751-1199
E-mail: sales@protech.com.tw
<http://www.protech.com.tw>

Protech Technologies Inc.

950 Fee Ana St, Suite B Placentia, CA 92870
TEL: +1-714- 996-7200 FAX: +1-714- 996-7300
Sales: sales@protech-usa.net
<http://www.protech-usa.net>

Protech Japan Co., Ltd.


OSK Bldg, 6F, 6-25-14, Minami-ohi Shinagawa-ku, Tokyo, 140-0013
TEL: +81-3-5753-8411 FAX: +81-3-3763-9282
E-mail: sam@protech-j.com
<http://www.protech-j.com>



ISO CERTIFIED
9001 14001

PSB-873LF

PICMG 1.3 Full Size CPU Card supports 3rd/2nd Gen. Intel® Core™ i7/ i5/ i3 Pentium® CPU with VGA/ Audio/ LAN/ 2COM



Specifications

System	
CPU Support	3rd/2nd Gen. Intel® Core™ i7/ i5/ i3 Pentium processor
CPU Frequency	3.0 ~ 3.4GHz
Chipset	Intel® H61
DRAM	2 x 240-Pin DDR3 DIMM, support dual channel memory 1333 / 1600MHz up to 16GB
BIOS	AMI
Watchdog	1~255 secs Watchdog timer selectable
Power Supply	Support ATX Power
Power Requirement	+5V, +12V, +3.3V, +5Vsb
Dimension	338.5mm x 126mm (13.33" x 4.96")
Certificate	FCC / CE

I/O Chipset

SATA Interface	4 x SATAII connector
Expansion BUS	Mini PCIe
Serial Port	2 x COM port, COM 1 for RS232, COM 2 for RS232/422/485
Parallel Port	1 x port
Keyboard	Mini DIN connector or external connector
Mouse	Mini DIN connector (selectable w/ KB) or Y-cable
LAN	Single Ports: support to 10/100/1000Mbps LAN1: Intel® 82579LM Supports Wake-on-LAN with ATX power

Audio	HD Audio, Realtek ALC888S
DI/O	4 in / 4 out
USB	8 x USB 2.0

Display

Graphics	Build-in processor, share memory, Support, 1 x VGA 2 x Display port
-----------------	---------------------------------------------------------------------------

*Discrete graphic card is necessary for display if the chosen CPU doesn't have integrated graphics support.

Environment

Operation Temp.	0° ~ 60° C (32° ~ 140° F)
Storage Temp.	- 40° ~ 85° C (- 40° ~ 185° F)
Humidity	Operation humidity 20 ~ 90%, storage humidity 20 ~ 95%

*All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information.

Ordering Information

BF-0873RA-00P	PICMG 1.3 Full Size CPU Card with Intel® CPU(LGA1155)+ H61 Chipset /VGA/Audio/ LAN(GbE)/2COM
----------------------	----------------------------------------------------------------------------------------------

All of trademarks and brand names are the property of their owners. Trademark "Protech" is the property of Protech Systems Co., Ltd. All information contained in this document is subject to change without any prior notice. This catalog is copyrighted in May 2013.