SE-8122 RoHS







Slim and Fanless Embedded PC









Features

- Intel[®] N2800/D2550 processor
- Fanless and compact size PC
- Maximum support 2 x LAN, 6 x USB2.0 and 4 x Serial port, 4 in/ 4 out Digital IO, 1 x SIM card slot
- Support wide temperature 0°C ~ 55°C (for Wide temperature CFast card)
- Support 9~36V wide range DC -in

Specifications

System

CPU Support	Intel®N2800/D2550 CPU on board
Chipset	Intel® NM10
Memory Support	1 x DDR3 SO-Dimm socket up to 4GB memory
Watchdog	1~255secs Watchdog timer selectable
Driver Bay	1 x 2.5 inch SATA HDD or SSD driver space support
Power requirement	9~36V DC-in
Power Adaptor	24V,72W power adaptor (optional)
Operating System	Win7(32-bit)
Expansion Slot	1 x CFast slot , 1 x mini-PCle slot, 1 x SIM card slot
System Weight	2 Kg
Dimension (W x H x D)	217.5 x 45 x 148 mm
Certificate	FCC / CE

I/O Ports (Front side)

USB	4 x USB2.0	
Serial Port	2 ports support (COM 3/4 for RS232)	
Digital I/O	4in / 4out	

I/O Ports (Rear side)


Display	1 x DVI-I
USB	2 x USB2.0
Audio	1 x Line out, 1 x Mic in
LAN	2 x 10/100/1000 LAN
Serial Port	2 ports support (COM1 for RS232, COM2 for RS232/422/485, COM1/2 RI/5V/12V selectable)
SIM card	1 x SIM card slot

Environment


Operation Temp.	HDD:0°C ~45°C (32°F~113°F)(with Airflow) Wide temperature CFast card:0°C ~ 55°C (32°F~131°F)(w/o Audio) (with Airflow)
Storage Temp.	- 20°C ~ 70°C (- 4°F~158°F)
Humidity	20% ~ 90%

^{*} All information contained in this document is subject to change without prior notice. Please log on www.protech.com.tw to acquire latest information. For detail mechanics drawing, please contact our sales.

System Front View



System Rear View



Ordering Information		
Order No	Description	
SE-8122RB-A0B	Intel® N2800 CPU + 1 x DVI-I + 4 x COM + 2 x LAN + 6 x USB2.0 + 1 x D I/O(4in/4out) + 1 x SIM card slot	
SE-8122RB-B0B	Intel® D2550 CPU + 1 x DVI-I + 4 x COM + 2 x LAN + 6 x USB2.0 + 1 x D I/O(4in/4out) + 1 x SIM card slot	
SE-8120RZ-WM1	Wall mount Kit	
SE-8122RZ-DIN	DIN Rail mounting Kit	
SE-8120RZ-WL1	Wi-Fi kit	
52-002-11072302	72W, 24Vdc output power adaptor	

^{*} CPU, DDR, Slim HDD are available as optional items

Applications

Factory Automation