

SRT-25BP-v1

5.0" IP67 Rugged Handheld
Terminal with NFC



The specifications listed in this document are subject to change without prior notice.

14th May 2016



1. General Description

1.1 Overview

The SRT-25BP-v1 is a 5" IP67 rugged handheld terminal with Gorilla Glass III, designed for data collection in extreme environments. The unit runs on the Android 4.4.2 O/S system, the display has a resolution of 720 x 1280 pixels and there is a 5-point multi-touch sensor fitted.

1.2 General Specifications

Panel Details	Size	5" Diagonal
	Native Resolution	720 x 1280
	Brightness	500 cd/m ² (Typ.)
	Touch Screen	5-point Capacitive w/ Corning Gorilla Glass III
Board Details	CPU Type	ARM Cortex-A7 1.3GHz (x4)
	GPU Type	Mali 400MP
	Memory	1GB DDR2 RAM / 8GB ROM
	Storage	Micro-SD up to 64GB (option)
Communications	2G/3G Band	WCDMA 850/1900/2100 GSM 850/900/1800/1900
	3G	WCDMA 3.75G (HSDPA+ 42.2Mbps, HSUPA+ 11.5Mbps)
	EDGE	Yes
	GPRS	Yes
	WAP	Yes
	WiFi	802.11B/G/N
	Bluetooth	BT4.0 / A2DP + EDR
	NFC	NXP547
Camera		8.0MP + AF & Electroflash
Software	O/S	Android KitKat 4.2.2
Sensor	Ambient Light Sensor	Yes
	Proximity Sensor	Yes
	Magnetic Field Sensor	Yes
Ports & Battery	Battery	4000mAh (Li)
	Wireless Charging	Qi Standard (Charging pad available)
	Sim Card	Yes (1.8 / 3.3W)
	Headphone	3.5mm jack
	USB	Mini-USB (Charge and Data)
External Functions	Navigation / Position	Support A-GPS/EPO (5-10M)

1.3 Mechanical and Environmental Specifications

Environmental Conditions	Operating Temperature	-20 to 60°C
	Storage Temperature	-40 to 80°C
	Operating Humidity	5 to 95% ^{RH}
	Operating Altitude	4500m (15,000ft)
Certification	Vibration	1-19Hz/1.0mm; 19-200Hz/1.0g
	Drop	MIL-STD-810G / Method 516.6 / Procedure IV
	Water/Dust	IP67
	CE / RoHS / FCC	Yes
Reliability	MTTF	50,000hrs (typ.)
	MTTR	<0.5h (typ.)
Weight		250g (with battery)
Outer Dimensions	Width	154mm
	Height	84mm
	Depth	17mm

* Specification is subject to change without prior notice.

2. Images

